Controlled gas exposure testing adds a direct measurement to cement system qualification tests

Chandler Engineering October 01, 2026

SPONSORED CONTENT

During the transition of cement from a pumpable slurry to a solid state, maintaining and confirming a gas-tight cement seal is essential. If gas migration does occur it can require costly remediation, well integrity issues, and pose safety risks. That raises a series of important questions for cement design and qualification. Such as “When does a cement system become vulnerable to gas invasion? How long does that vulnerability persist for? Does the cement maintain pressure isolation while hydration is occurring?”

Laboratory testing of gas exposure during the transition from liquid to solid helps answer these questions by directly evaluating cement performance under conditions that can lead to gas migration. Rather than solely relying on indirect indicators, controlled gas exposure testing provides a direct assessment of whether a cement system can maintain pressure isolation while hydrating. This helps turn a complex hydration process into a clearer design decision.



Fig. 1. 7200 Cement Hydration Analyzer System

UNDERSTANDING THE TRANSITION FROM SLURRY TO SOLID

Sometimes one of the most critical and uncertain phases of a primary cementing operation often begins once pumping has stopped. At this stage, the slurry has been placed in the annulus but has not yet developed into

Connect with World Oil

a solid barrier. Initially, the cement behaves as a fluid, transmitting full hydrostatic pressure throughout the cement column. As hydration progresses, the slurry begins to gel and develop structural strength. Over time, the cement becomes increasingly capable of supporting its own weight, resulting in a gradual reduction in pressure transmission through the slurry.

This transition period is important because the cement has not yet developed the properties of a fully set barrier. Fluid loss to the formation along with shrinkage can contribute to a reduction in cement pore pressure. If pore pressure falls below the pressure of an adjacent gas bearing formation, gas may enter the column and create channels.

These channels cannot be described by a single cement property, but through a combination of different tested properties. Thickening time describes the period at which the slurry remains pumpable. Static gel strength characterizes development of structure within a slurry. Compressive strength measures information about the development of the hardened cement. Each measurement answers important questions, but none directly observes how a hydrating cement sample responds when subjected to external gas applied to the cement.




Fig. 2. The cell for the cement hydration analyzer showing where gas is injected and water confining pressure, along with where pore pressure and temperature are monitored.

The 7200 Cement Hydration Analyzer (CHA), **Fig. 1**, was designed to directly observe how a hydrating cement sample responds to an applied gas pressure differential during the transition from slurry to solid. In simple terms, the CHA measures whether a hydrating cement system maintains pressure isolation when subjected to a controlled gas pressure challenge.

MEASURING THE PRESSURE RESPONSE OF HYDRATING CEMENT

The measurement performed by the CHA is relatively straightforward. A cement sample is placed inside a pressure vessel and subjected to controlled temperature and pressure conditions, **Fig. 2**. During the hydration phase of the cement slurry, nitrogen can be introduced at the bottom end of the cement slurry while pore pressure is measured at the opposite end. The experiment then establishes a pressure differential across the hydrating cement.

The instrument then monitors whether the applied gas pressure is transmitted through the hydrating cement sample by observing changes in pore pressure and gas flow response. In one outcome, the cement develops sufficient isolation and the nitrogen pressure applied at the bottom of the sample is not transmitted to the pore pressure measurement at the top. The graph will then show that the pore pressure continues to decrease or stay the same after initial cement gelling and the H_2O confinement pressure is gradually isolated, **Fig. 3**. This shows a cement slurry that passed the test and is good to go.




Fig. 3. Showing when gas migration occurs due to the increase of the pore pressure after initial hydration. This indicates that gas migration is occurring.

In the second scenario, gas migrates through the cement structure. As this occurs, the measured pore pressure begins to rise after an initial decline caused by cement gelation and the gradual isolation of the H_2O confining pressure. This increase in pore pressure indicates slurry failure and confirms that gas migration is occurring through the cement, **Fig. 4**.

The instrument records several variables simultaneously such as cement pore pressure, nitrogen injection pressure, cement temperature, H_2O Confining pressure, flow rate, and elapsed time. The value of the experiment comes from examining the relationship among the measurements rather than interpreting any individual curve independently. It also uses inexpensive disposable cylinder bodies for the cement sample as well as allowing unattended operating of testing after initial setup.

The CHA enables evaluation of multiple gas migration scenarios, ranging from severe to less severe cases. Its flexible configuration supports a variety of testing conditions, providing a more comprehensive understanding of potential downhole environments and gas migration behavior.




Fig. 4. Showing when gas migration does not occur as the pore pressure remains relatively constant. Showing a go case scenario of a cement slurry.

The flow rates can also be used as raw data to make an approximate calculation of shrinkage or expansion of the cement and the volume of gas which entered the cement sample.

One of the principal differences between the CHA measurement and a conventional endpoint measurement is that the instrument is observing a dynamic process rather than simply determining a property after a specified curing period.

The sequence may show the slurry heating to the programmed test condition and initial pressure equilibrium, followed by gradual pore pressure decline and development of the hydration temperature response. Lastly, when nitrogen is introduced, the system may show either continued pressure isolation or pressure communication.

Viewing these measurements on a common time axis helps distinguish the various stages of the experiment. The CHA is not simply a gas flow apparatus but a multi parameter system for observing how pressure transmission changes as cement hydrates.

COMPARATIVE EVALUATION OF CEMENT FORMULATIONS

One of the most useful applications of the instrument is comparative testing. When considering between two cement formulations intended for the same well conditions, the CHA can subject both formulations to the same gas exposure protocol while the laboratory controls variables such as slurry preparation and testing conditions.

This allows the engineer to evaluate how different formulations respond to the same pressure challenge during hydration.

HOW THE CHA DIFFERS FROM ULTRASONIC CEMENT ANALYSIS (UCA)

The CHA addresses a different measurement than the UCA. The UCA monitors changes in ultrasonic transmission through cement as the material cures. Those measurements correlate with compressive strength development and provide information about when the cement begins developing strength.

The CHA examines a different aspect of cement behavior. Rather than measuring strength development, it evaluates whether the hydrating cement can maintain pressure isolation when challenged by an applied gas pressure differential. Instead of asking, "How quickly is the cement developing compressive strength?" the CHA experiment asks, "Does the hydrating cement maintain pressure isolation when exposed to a controlled gas pressure differential?"

The distinction is significant because mechanical strength development and hydraulic isolation are related but do not have identical properties. A cement system can develop strength while simultaneously undergoing pore pressure reduction, shrinkage, and changes in permeability.

For this reason, UCA and CHA measurements should be considered complementary rather than interchangeable. Together with thickening time, rheology, fluid loss, and static gel strength, these measurements provide a broader description of cement performance.

APPLYING CHA RESULTS TO CEMENT SYSTEM QUALIFICATION

The CHA does not reproduce an entire wellbore. Instead, it isolates several variables associated with gas migration and places them under controlled laboratory conditions.

Connect with *World Oil* ▲

The purpose of the CHA is therefore not to predict a specific field migration distance or determine the minimum required cement column length directly. Its purpose is to characterize how a cement formulation responds to a defined gas pressure challenge while hydration is occurring, with a go/no-go response indicator. Field interpretation still requires the laboratory results to be combined with well-specific cementing analysis.

The forward path is not to replace established methods, but to connect them. Laboratory qualification, well-specific modeling, placement surveillance, and post-job cement evaluation each answer a different part of the barrier question.

Controlled gas exposure testing can help engineers reject vulnerable formulations earlier, compare alternatives on a consistent basis, and document the reasoning behind a cement system decision.

CONCLUSION

The value of the CHA is not that it replaces existing cement tests, but that it measures the behavior those tests do not directly observe. By monitoring the pressure response of a hydrating cement sample during controlled gas exposure, the instrument provides a direct assessment of pressure isolation development during one of the most critical stages of a cement job. When combined with conventional cement laboratory testing, the CHA contributes to a more complete understanding of barrier performance and gas migration risk.

CUTLINES:

Fig. 1. 7200 Cement Hydration Analyzer System

Fig. 2. The cell for the cement hydration analyzer showing where gas is injected and water confining pressure, along with where pore pressure and temperature are monitored.

Fig. 3. Showing when gas migration occurs due to the increase of the pore pressure after initial hydration. This indicates that gas migration is occurring.

Fig. 4. Showing when gas migration does not occur as the pore pressure remains relatively constant. Showing a go case scenario of a cement slurry.

©2026 World Oil, © 2026 Gulf Publishing Company LLC.
Copyright © 2022. All market data is provided by Barchart Solutions.
Futures: at least 10 minute delayed. Information is provided 'as is' and solely for informational purposes, not for trading purposes or advice. To see all exchange delays and terms of use, please see disclaimer.

All material subject to strictly enforced copyright laws
Please read our Terms & Conditions, Cookies Policy and Privacy Policy before using the site.
Do Not Sell or Share My Personal Information.

Connect with *World Oil*